

Thank you and congratulations for purchasing this updated, advanced, Emergency GMRS Two-Way Radio & Scanner.

The **WOUXUN KG-UV9GX+** is a new entry in the famous UV9-Series line, built upon the trusted performance, proven design, and quality manufacturing of the UV9D(Plus) & UV9GX amateur radios. It has been updated to deliver improved commercial-grade personal, personal business, recreational, hobby, group safety, CERT, emergency (EmComm), and SHTF/Disaster communications & scanning.

COMPLIANCE

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with PART 15B of the FCC Rules.

Operation is subject to the following two conditions:

- 1) This device may not cause harmful interference, and
- 2) This device must accept any interference received, including interference that may cause undesired operation.

WARNING: MODIFICATION OF THIS DEVICE TO RECEIVE CELLULAR RADIOTELEPHONE SERVICE SIGNALS IS PROHIBITED UNDER FCC RULES AND FEDERAL LAW.

This device meets the requirements of FCC PART 15.121(b) for scanning receivers in the following frequency ranges (in MHz): 76–108 / 108–136 136–180 / 219–250 / 350–400 / 400–512 / 700–824 / 849–869 / 894–960

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 2.5 cm between the radiator and your body. The antenna used for this device must not be co-located or operating in conjunction with any other antenna or transmitter.

CAUTION: Do not transmit without an antenna attached, with a damaged antenna, while touching the antenna, around explosives, or while refueling a vehicle. Operate only with batteries & chargers designed for this radio.

MAIN FEATURES

- **5X Display Brightness for Improved Readability Outdoors!**
- **3 “Dark” Display Modes** • **Priority Channel Quick-Jump**
- **2200 mAh USB-C Battery** (w/ Adapter & 6' Cable) • **Scan Advance**
- **1.25 meter HAM “220 Band” Rx** • **3 Power Levels & U.S. Calibration**
- **999 Memory Channels** • **Brighter LED Flashlight** • **Stiff Knobs**
- **Pre-Programmed for GMRS + SHTF (906 Channels)** • **VFO**
- **Emergency RESET** (44 Chan. incl. GMRS/HAM/NOAA/MMS/AIR/SAR)
- **Analog TDR Superheterodyne FM GMRS** • **Duplex Operation**
- **FPP** • **Dual-PTT** • **BCL** • **VOX** • **Speaker & Sub-Receiver Muting**
- **DTMF Keypad** • **Simplex & Repeater Capable** • **Wide & Narrow BW**
- **7-Band Rx w/AM AIR Band & Broadcast FM Radio** w/20 Memories
- **Roger Beep** • **3 Scan Modes** • **10 Scan Groups** • **Priority Scanning**
- **Dual Simultaneous Channel & VFO/Frequency Scanning**
- **Single & Dual-Watch Modes** • **Repeater Reverse & Talk-Around**
- **CTCSS/DCS Search/Scanning** • **Stopwatch** • **2.5 kHz Tuning Steps**
- **155 Split CTCSS/DCS PL Tones/Codes** • **8-Character Alpha Names**
- **Dual Indicator LEDs** • **Backlight Timer/Dimmer** • **5 Backlight Levels**
- **3 Programmable Function Side-Keys** • **Manual & Auto Key/PTT Lock**
- **Key Beeps** • **Voice Announce** • **ANI PTT-ID** • **Time-Out-Timer**
- **10 Squelch Levels** • **Squelch Monitor** • **Squelch Tail Eliminator**
- **Battery Saver** • **Battery Voltage Meter** • **8” GMRS-Tuned Antenna**

FEATURE ADDITIONS & IMPROVEMENTS

The following features have been added, modified or improved upon over the original KG-UV9D(Plus) & KG-UV9P amateur radios, on which the UV9GX+ is based.

- **5X Display Brightness:** The UV9GX+ color TFT display now has 5 times the brightness output (**1000CD**, perceived as at least 2X brighter) for improved readability outdoors or in very bright light. The output can be reduced with **[MENU 27_ABR-LV | 01-05]** for indoor use.
- **USB-C Charging:** A 2200 mAh USB-C Li-ion battery is included as standard with a USB-C AC Adapter & USB-C charging cable. (Optional 2000 mAh & 3200 mAh batteries available separately.)

Note: The Cross-Band Repeater feature is not available on the GMRS band. The Repeater Offset/Direction features are only available via software or channel copy.



KG-UV9GX+ GMRS

Two-Way Radio Transceiver & Scanner

FCC PART 95E & 15B Certified – FCC ID: WVTWOXUN19

FCC PART 95 WARNING

This device operates on GMRS (General Mobile Radio Service) frequencies, which require an FCC (Federal Communications Commission) license. You must be licensed prior to transmitting on these frequencies. Serious penalties could result for unlicensed use of GMRS frequencies in violation of FCC rules, as stipulated in the Communications Act's Sections 501 and 502 (amended). You will be issued a call sign by the FCC, which should be used for station identification when operating the radio on GMRS frequencies. You should also cooperate by engaging in permissible transmissions only, avoiding channel interference with other GMRS users, and being prudent with the length of your transmission time. To obtain a license or ask questions about the license application, contact the FCC at 1-888-CALL-FCC or go to the FCC's website: <https://www.fcc.gov> and request form 605.

STATION ID

Your GMRS call sign must be transmitted using voice in the English language, or with International Morse Code telegraphy using an audible tone: (a) Following a single transmission or a series of transmissions; and (b) After 15 minutes and at least once every 15 minutes thereafter during a series of transmissions lasting more than 15 minutes.

CAUTION: To avoid possible damage, avoid operating the radio or transmitting while charging via USB-C port or optional charger base, or when a USB programming cable is inserted (other than for programming).

CAUTION: This radio is rated IP55 for dust & “water jets.” Do not submerge or intentionally soak radio with any liquid (or gel).

TIP: For the longest life, remove battery from radio if storing for more than a couple weeks, with a 60% “shelf” charge. Do not store in a powered charger.

- **3 New Dark Display Modes:** Use **[MENU 62_SCN-MD]** to set 1 of 4 color screen modes with 3 new “dark” backgrounds:
 - **Classic:** Traditional Blue Text on White background.
 - **Covert:** Dark Red on Black background for minimal exposure.
 - **Day 1:** Bright Yellow on Black background for highest contrast.
 - **Day 2:** White on Black background for high contrast.
- **Priority Channel Quick-Jump:** *Long-Press* the **BAND** key to instantly switch to your Priority Channel on the A receiver, even while scanning. The function will halt activity on the A receiver (except while in Function or FM Radio Menus), leaving the FM Radio and B receiver uninterrupted. This is handy for setting an **emergency EmComm** or **CALL Channel** (default), a favorite “home” repeater or channel, **NOAA WX** station, or **Public Safety/Scanner** channel, etc.
- **Scan Advance:** If you encounter an unwanted signal while scanning in **TO/CO** Scan Modes, you can use the **Channel Knob** or **▲▼** keys in either direction to quickly advance/resume scanning (previously had to exit and scan again). See **Scanning** section for more details.
- **1.25 meter HAM “220” Band Rx:** Range now covers **219–250 MHz**.
- **Bright Flashlight:** Includes a brighter LED flashlight with tight beam.
- **Stiff Knobs:** The channel and volume knobs now have additional washers that provide more resistance, to help avoid accidental changes (can be removed for less resistance).
- **3 Power Levels:** **Low = 0.5 Watts | Mid = 2 Watts | High = 5 Watts**.
- **Pre-Programmed for GMRS + SHTF:** The UV9GX+ now comes pre-programmed with **906 channels**, including all GMRS/FRS channels with multiple repeater banks, HAM FM Call & Simplex frequencies, loads of general & SHTF receive-only channels such as NOAA Weather stations, MURS, MMS (Marine), AIR (Aviation), AAR (Railroads), SAR, and various national GOV emergency and other agency frequencies (not active in all areas).
- **Emergency RESET ALL:** The radio now defaults to 44 useful SHTF emergency channels after performing a **MENU RESET ALL** function. See the **DEFAULT CHANNEL PROGRAMMING TABLE** (below).

LCD DISPLAY DATA & ICONS

Row 1	TKA	Talk-Around (Simplex)
	VOX	Voice Operated Transmit Enabled
	S	Battery Saver Enabled
	LOCK	LOCK Mode Enabled (Keypad, Ch Knob, PTT, ALL)
	Battery Charge Level (100% shown)	
Row 2	C	Priority Scanning On (flashes after recent signal)
	FM or "MSG"	FM Radio On or Muted/Freq. or Personal Message
A/B Rec.	or	Receiver On or Muted
Top	QT or DT	Rx CTCSS or DCS Enabled (or Tx during transmit)
Row	T	DTMF Encoding/Decoding Enabled
	W or N	Wide or Narrow Modulation Bandwidth
	+ or -	Positive or Negative Repeater Tx Offset Direction
	R	Repeater Reverse Enabled (Swaps Rx/Tx Freqs)
	★	Priority Channel
	Call	Most Recently Received Call (signal or select call)
	MAIN	Currently Selected MAIN Receiver/Transmitter
A/B Rec.	GMRS 3E 003	Channel Name + Channel # (NAME Display Mode)
Center	462.61250	Frequency (FREQ-VFO Display Mode, in MHz)
Row	CH-003 003	Memory Channel # + Channel # (CH Display Mode)
	462.61250 003	Frequency + Channel # (CHFREQ Display Mode)
	7.40V	Battery Voltage Level (DC Volts) MENU VOLTAGE
	BCL	Busy Channel / Tx Inhibit when BCL Enabled
	FRQ OVER	Tx frequency is blank or outside of avail. Tx range
	00. 00. 00	SECOND (Stopwatch) Time (in HH. MM. SS)
	[FUNCTION/VALUE]	Various MENU Functions or Settings/Values
A/B Rec.	H or M or L	High, Middle or Low Tx Power
Bottom	Signal S-Meter or Tx Power	Rx (Signal) S-Meter or Tx Power (during transmit)
Row	AM	Amplitude Modulation Enabled (FM mode when off)

BASIC OPERATION

Key Presses: The **PF2** & **PF3** side-keys and several front panel keypad keys allow short and long presses (see below) to access primary and secondary functions (such as ***-SCAN** for the **Repeater Reverse/Scan** functions — see the **Programmable Function Keys** & **Keypad Shortcuts** sections above).

A quick momentary press or “**Short-Press**” (**SP**) activates the primary key function. A “**Long-Press**” (**LP**) involves holding down a key for about 1-2 seconds to activate the secondary key function.

Function Menu: Press the **MENU** key to enter the Function Menu. Use the **Channel Knob**, **▲▼** or **1-9** keys to select a function. Press **MENU** again to Edit the selected function. Use the same controls to select or enter a value, then press **MENU** again to write any changes. Press **EXIT** at any time to exit the function Menu or to abort the current Menu operation without saving changes for the currently selected function, or wait for the **MENU** to time-out (about 10 sec.).

Display Modes: Long-Press **TDR|V/M** to cycle through all 4 Display Modes:

- **NAME** (default): Displays the stored Name (if any) for the current memory channel, with the channel # to the right (in small text).
- **FREQ-VFO** (Variable Frequency Oscillator): For direct frequency tuning/input, scanning frequencies, or programming new channels. Acts like a traditional “digital” radio tuner.
- **CH:** Displays the Number for the current memory channel, with the channel # to the right (in small text).
- **CHFREQ:** Displays the frequency stored for the current memory channel, with the channel # to the right (in small text).

TIP: You can hold down the **▲▼** keys or use the **Channel Knob** to quickly scroll through channels, frequencies, or **MENU** functions/values.

TIP: You can use the **EXIT** key as a backspace key while entering a frequency in the **FREQ-VFO** Display Mode.

RADIO CONTROLS & INDICATORS

- Speaker/Mic **Audio & Programming** Jacks
- **On/Off/Volume** Knob
- **Rx Green Signal & Tx Red Transmit** LED Indicators
- **Channel Knob** (bi-directional; continuous)
- **Flashlight LED “LAMP”**
- **SMA-Female Antenna Connector**

PROGRAMMABLE FUNCTION KEYS

Default PF Side Key Assignments:

- **PF1 LP: Sub-Rec. PTT** (Transmit - mom.)
- **PTT LP: MAIN Tx** (Transmit - mom.)
- **PF2 SP: FM Radio** (On/Off)
- **PF2 LP: Flashlight/Torch** (On/Off)
- **PF3 SP: Monitor** (Open/Close Squelch)
- **PF3 LP: Stopwatch** (LP: Start/ SP: Stop/SP: Off-Reset)

KEYPAD SHORTCUTS

- **BAND SP:** Toggle Active **MAIN** Receiver | **LP: Priority Channel Quick-Jump**
- **TDR|V/M** Display Modes
SP: **Single/True Dual Receive**
LP: **FREQ-VFO/CH/CHFREQ/NAME**
- **MENU:** Access Radio Functions/Settings | Press again to **Edit**, then again to **Save**
- **EXIT:** Exit Menu or Cancel Scanning
- **1-9: Freq/Chan Entry** | **FM Radio Memories** | **Menu Function Shortcuts**
- ***-SCAN SP: Repeater Reverse** | **LP: Start Scan Mode**
- **#-LOCK SP: IN FRQ/SAVE/CALL (FM Radio)** | **LP: LOCK**
- **▲▼ SP/LP: Next/Prev. Channel/Function/Value/Scan Direction**
- **RPT SP: Change Band** (in VFO) | **LP: Talk-Around/Direct** (simplex)



Receiving (Rx): Turn the radio on by rotating the **On/Off/Volume Knob** clockwise. Use the **Channel Knob**, **▲▼** or **1-9** keys to select the desired channel. Adjust the **Volume Knob** as desired.

- **Main:** Toggle the active **MAIN** receiver with the **BAND** key.
- **Single/True Dual Receive:** Toggle **Single** or **True Dual Receive** Modes with the **TDR|V/M** key.
- **Sub-Receiver Muting:** You can choose if you want audio on the Sub-Receiver (opposite of **MAIN**) muted (while in **TDR** mode) when a signal is received (even while scanning), or when you transmit on the **MAIN** receiver, or both. Use [**MENU 60_S-MUTE** | **OFF, RX-MUTE, TX-MUTE, R/T-MUTE**] to toggle.
- **Rx CTCSS:** Set **CTCSS** tones or **DCS** codes (sometimes referred to as “PL Tones” or “Privacy/Quiet Tones”) with [**MENU 16_Rx-CTC**] or [**MENU 18_Rx-DCS**] to mute the receiver unless a signal includes the specified tone/code. Setting one Rx type will remove the other.
- **SQUELCH:** Set with [**MENU 08_SQL-LE** | **0-9**] to mute the speaker for background noise or signals below the certain level. A squelch level of 5 or 6 is usually a good starting point.

Note: The top A Receiver can tune/scan all 7 bands available. The B Receiver covers only the normal dual-band “UV” range: 136-174.9975 MHz & 400-512.9975 MHz.

Transmitting (Tx): Choose the desired channel or frequency. **SP PF3 Monitor** to confirm channel is not in use, then again to mute.

Hold the radio upright/vertical a few inches from your mouth with the display facing you or at a slight angle.

Press & hold the **PTT** key, pause for about one second, then speak at a normal, consistent volume. Release the **PTT** key to stop transmitting. The radio will immediately return to receiving.

- **Tx CTCSS:** Set **CTCSS** tones or **DCS** codes with [**MENU 17_Tx-CTC**] or [**MENU 19_Tx-DCS**] to transmit a sub-audible tone/code with your signal to other stations, or to access repeater stations. Setting one Tx type will remove the other.

Transmitting (Tx) (continued):

- **Roger Beep:** Set to transmit a tone at the beginning or end of your transmission (or both) with [MENU 15_ROGER]. The EOT (End Of Tx) setting is most commonly used so other stations know when your transmission is over, instead of saying “OVER.” It’s typically discouraged while operating on GMRS repeaters.
- **Busy Channel Lockout:** Avoid accidentally transmitting when there’s an active signal detected (useful when Rx CTCSS or DCS is set) with [MENU 18_BCL].

Broadcast FM Radio: The Commercial **FM Radio** feature tunes from 76 to 108 MHz in 100 kHz steps. It offers an VFO Mode (**IN FRQ**) with **SE** Search Scanning, Memory **SAVE**, and Memory re**CALL** functions with 20 dedicated memories. When operating the **FM Radio**, the **MAIN** & Sub-Receiver (if in **TDR** Mode) will be “watching” for active signals and will mute the **FM Radio** and play the **MAIN** or Sub-Receiver signal audio instead. When the signal ceases, the **UV9GX+** will resume playing the current **FM Radio** station, until the feature is turned off.

- Enter the **FM Radio** feature with **SP PF2**. Do the same to exit.
- Toggle between **IN FRQ/SAVE/CALL** modes with **SP #-LOCK**.
- Press the ***-SCAN** key to scan for an active **FM Radio** station.
- Use the **1–9** keys or **Channel Knob** to enter/select a frequency or memory channel in **IN FRQ/CALL** modes, then press the **MENU** key to commit the entry/selection.

Scanning: To start scanning memory channels or frequencies on the current **MAIN** receiver, use **LP *-SCAN** key, or optionally assign “SCN” to a **PF Side Key**. See the three **Scan Review** Modes to the right.

To start scanning on the other receiver, press the **BAND** key to switch the **MAIN** receiver, then **LP *-SCAN** key. Use [MENU 60] to control Sub-Receiver Muting and **BAND** key to select primary (**MAIN**) receiver.

To exit **Scanning** on an active channel/frequency, switch to the desired **MAIN** receiver with **SP BAND** key, then press any other key (other than **▲▼** and **BAND**), such as **EXIT**, **0–9**, or ***-SCAN**.

Adding New or Copying Existing Memory Channels: You can add new simplex GMRS Tx/Rx channels or copy existing repeaters, or add Rx-Only Scanner channels to any memory with the keypad, as desired.

- **Add New Simplex or Scanner Channels:**
 - Switch to the **FREQ-VFO** Display Mode (see above).
 - Use the **Channel Knob**, **▲▼** or **1–9** keys to select/enter the desired frequency (radio will auto-complete trailing zeros).
 - Set any other desired parameters in the **Function Menu**.
 - Write the VFO to a channel with [MENU 30_MEM-CH | 001–999]. New/unused channels are indicated in an alternate color. (See **Basic Operation – Function Menu** instructions.)
- **Copy Existing Simplex/Repeater/Scanner Channels:**
 - Switch to the **CH**, **CHFREQ** or **NAME** Display Mode.
 - Use the **Channel Knob**, **▲▼** or **1–9** keys to select/enter the desired channel to copy.
 - Write the channel to a new memory with [MENU 30_MEM-CH]. New/unused channels are indicated in an alternate color. Repeater settings will be retained, including the Offset Freq. & Direction. You can rename the new channel (see below).
- Switch to **CH**, **CHFREQ** or **NAME** Display Mode and use the **Function Menu** to set any desired parameters, such as **W/N**, **TXP**, **BCL**, **Rx-CTC/DCS**, **Tx-CTC/DCS**, **CH-NAME**, or **SCAN-ADD**, etc., to customize the new or copied memory channel.
- While setting a **Channel Name** with [MENU 29_CH-NAME], use the **Channel Knob**, **▲▼** or **1–9** keys to select/enter a character/number, **#-LOCK** to accept and move forward, and **EXIT** to move back. When done, press **MENU** to write the new name, or **LP EXIT** to abort without writing. You can use up to 8 characters.

Note: Some Menu Functions can only be set in specific Display Modes: **SCN-ADD** & **CH-NAME** are only available in the **NAME**, **CH** & **CHFREQ** Modes, **OFFSET** in the **FREQ-VFO** Mode, and **SFT-D** via software only (indicated in **Function Menu Options** table below).

The **UV9GX+** offers single or dual receiver scanning of all 999 memory channels with three available **Scan Review** Modes set independently for each receiver via [MENU 20_SC-REV | TO/CO/SE].

- **TO Timer Scan Review** Mode: Scans until a signal is received, pauses for 5 seconds to preview audio, then resumes scanning.
- **CO Carrier Scan Review** Mode: Scans until a signal (carrier) is received, pauses until it ceases, then resumes scanning if no new signal is detected within 3 seconds.
- **SE Search Scan Review** Mode: Scans (searches) for the first signal that “opens” the set squelch level, then exits **Scanning**, remaining on the current channel or frequency.
- **Scan Group:** Set the active Scan Group (10 avail., defined in **CPS**) independently for each receiver. Use **SP BAND** to select the desired **MAIN** receiver, then set with [MENU 49_SCN-GP | 01–10].
- **Scan Advance:** If you encounter an unwanted signal while scanning in the **TO** or **CO** Scan Modes, use the **Channel Knob** or **▲▼** keys to instantly advance/resume scanning in either direction.
- **Priority Scan:** When “ON” [MENU 33_PRI-SCN], checks Priority Channel [MENU 32_PRI-CH] for a signal every 1–2 seconds on the **MAIN** receiver, when not in regular Scanning Mode on that receiver.

PROGRAMMING VIA COMPUTER

You can program channel data and most radio menu settings on your **UV9GX+** via computer with the free **WOUXUN** Customer Programming Software (**CPS**) and the “Red” PCO-009 USB Programming Cable (sold separately at BSR) & free USB driver software, available at BetterSafeRadio.com/UV9GX+.

For more advanced editing features, the **RT Systems** UV9G Advanced Programming Software & USB Cable Kit (sold separately at BSR) can be used instead (excluding the Dark Display Modes).

Or use the free open-source **CHIRP** programming software (search for “CHIRP my radio” on the web), including to customize the “**BetterSafeRadio**” Personal Display Message (16 char. max.).

TIP: Search for local repeaters & request permission at myGMRS.com.

DEFAULT CHANNEL PROGRAMMING TABLE

The following 44 emergency SHTF channels are restored after performing a **MENU RESET ALL** function [MENU 61_RESET | ALL].

Ch	Name	Rx Freq.	Tx Freq.	Ch	Name	Rx Freq.	Tx Freq.
001	GMRS 01C	462.562s	462.562s	023	GMRSr15	462.550	467.550
002	GMRS 02S	462.587s	462.587s	024	GMRSr16S	462.575	467.575
003	GMRS 03E	462.612s	462.612s	025	GMRSr17	462.600	467.600
004	GMRS 04	462.637s	462.637s	026	GMRSr18	462.625	467.625
005	GMRS 05	462.662s	462.662s	027	GMRSr19	462.650	467.650
006	GMRS 06	462.687s	462.687s	028	GMRSr20T	462.675	467.675
007	GMRS 07	462.712s	462.712s	029	GMRSr21	462.700	467.700
008	GMRS 08	467.562s	467.562s	030	GMRSr22	462.725	467.725
009	GMRS 09S	467.587s	467.587s	981	NOAA WX1	162.550	Rx Only
010	GMRS 10	467.612s	467.612s	982	NOAA WX2	162.400	Rx Only
011	GMRS 11	467.637s	467.637s	983	NOAA WX3	162.475	Rx Only
012	GMRS 12	467.662s	467.662s	984	NOAA WX4	162.425	Rx Only
013	GMRS 13	467.687s	467.687s	985	NOAA WX5	162.450	Rx Only
014	GMRS 14	467.712s	467.712s	986	NOAA WX6	162.500	Rx Only
015	GMRS 15C	462.550	462.550	987	NOAA WX7	162.525	Rx Only
016	GMRS 16S	462.575	462.575	988	NOAA WX8	161.650	Rx Only
017	GMRS 17E	462.600	462.600	989	NOAA WX9	161.775	Rx Only
018	GMRS 18	462.625	462.625	991	MMS 16EM	156.800	Rx Only
019	GMRS 19	462.650	462.650	992	AIR EM	121.500	Rx Only
020	GMRS 20T	462.675	462.675	993	SAR EMT	155.160	Rx Only
021	GMRS 21	462.700	462.700	995	2m HAM	146.520	Rx Only
022	GMRS 22	462.725	462.725	996	70cm HAM	446.000	Rx Only

(Tx-CTC “PL Tone” of 141.3 on all GMRS channels except 210.7 on chs. 2 & 16)

C = CALL S = Safety EM/E = Emergency/Prepper T = Travel r = Repeater
NOAA = National Weather Service MMS = Maritime Marine
AIR = Aviation (AM) 2m/70cm = VHF/UHF HAM Band CALL Frequencies
SAR EMT = Search & Rescue / Emergency Medical Technicians

Function Menu Options & Descriptions 01–17

01	ABR:s Auto Backlight Timer	OFF 1S–30S ALWAYS ON (in seconds) Duration LCD backlight remains on after any activity.
02	SAVE Battery Power Saver	OFF 1–4 (1=2:4, 2=2:6, 3=2:8, 4=3:9 – in 100mS) Receiver duty-cycling to save battery life. Set #4 in software.
03	STEP Tuning Step	2.5K 5K 6.25K 8 10K 12.5K 20K 25K 30K 50K 100K Tuning step for FREQ-VFO Display Mode in kHz.
04	W/N Modulation Bandwidth	WIDE NARR (16 kHz 11 kHz) Rx/Tx modulation bandwidth for 25k / 12.5k channels.
05	TXP Transmit Power	LOW MIDDLE HIGH (0.5 Watts 2 Watts 5 Watts) RF output power level for Tx (transmit).
06	SFT-D (in software only) Tx Shift Direction	Disabled for GMRS compliance. (always + Dir. on GMRS) Copy existing repeater to new memory channel to clone.
07	VOX Voice-Operated Transmit	OFF 01–10 (01 is highest sensitivity) Sensitivity for automatic Tx based on microphone voice level.
08	SQL-LE Squelch	0–09 (0 = OFF/OPEN) Signal strength threshold for squelch speaker muting.
09	ROGER Roger Beep	OFF BOT EOT BOTH (B = Beginning, E = End Of Tx) Courtesy “OVER” tone during Tx. Excluding repeaters.
10	TOT:s Time-Out Timer	15S–180S (in 15 second increments) Timer for automatic Tx shutoff to protect transmitter.
11	TOA:s Time-Out Timer Alarm	OFF 01S–10S (in seconds) LED warning flashing time before TOT expires.
12	VOICE-SW Voice Announce/Prompt	OFF ON Voice announcements/prompts.
13	BEEP Key Beep	ON OFF Audible keypad & function key confirmation tone.
14	MENULANGE Menu Language	Disabled. Always set to ENGLISH.
15	BCL Busy Channel Lockout	OFF ON Tx inhibit when active signal detected on channel/freq.
16	Rx-CTC Cont. Tone-Coded Squelch	OFF 67.0Hz–254.1Hz (or non-standard values via keypad) Rx CTCSS “PL/Quiet Tone” decoding for speaker muting.
17	Tx-CTC Cont. Tone-Coded Squelch	OFF 67.0Hz–254.1Hz (or non-standard values via keypad) Tx CTCSS “PL/Quiet Tone” encoding during transmit.

Function Menu Options & Descriptions 34–53

34	AUTOLOCK Auto-Lock	OFF ON Enables LOCK mode after 15 seconds of no activity.
35	LOCKMODE Lock Mode	KEY-LK KEY+PG KEY+PTT ALL Keypad + PF keys, or + Ch. Knob, or + PTT (Rx-only), or all.
36	S-TONE Single-Tone Tx “Tone-Burst”	1000H 1450H 1750H 12100H (in Hz, press PF3 while Tx) Frequency of Single-Tone Tx (for repeater access).
37	VOX-DLY:s VOX Transmit Delay	OFF 01S–05S (in seconds) Duration Tx continues after microphone audio/voice stops.
38	SC-QT Save Coded Quiet Tone	R-QT T-QT R&T-QT (Rx–CTC/DCS TX Both) Where found CTC/DCS tone is saved after SCN-CD search.
39	APO-TMR Auto-Power-Off Timer	OFF 15M–150M (in 15 minute increment) Timer for auto power off if no keypad or channel knob use.
40	PONMSG Power-On Message	BATTY BITMAP (BITMAP only active if factory image set) Battery DC Volts or custom image during radio power-up.
41	BLCDSW Backlight LCD Switch	OFF ON Dims LCD backlight instead of turning off completely.
42	BLEDSW Backlight LED Switch	OFF ON Flashes status LED when LCD is off to indicate radio is on.
--	MENU 43–47	Settings for Cross-Band Repeater not used on GMRS radio.
48	SCN-ADD (ch mode only) Scan Add Channel	OFF ON Disable or enable scanning of currently selected channel.
49	SCN-GP Scan Group	01:name – 10:name ALL (Scan Groups set via software) Set active Scan Group, or all channels, for each receiver.
50	SCN-MODE Scan Range Mode	ALL Cur Region Lmt Frq (Limit Freqs. set via software) Limit FREQ-VFO scanning to all, current band, or limit freqs.
51	SCN-CD Scan CTCSS/DCS	CTCSS DCS (Use Ch. Knob or ▲▼ to change scan dir.) Scan for CTCSS or DCS tone/code on active signals.
52	CALL ID Select Call ID	01:name – 20:name (Call ID Group Names set via software) Select Calling ID (Group) to Tx (if CALL enabled on a PF key).
53	AUTO-AM Auto-AM Receiver Mode	OFF ON (Activates AM Mode when AM signal detected) Disable or enable automatic AM Mode detection switch.

Function Menu Options & Descriptions 18–33

18	Rx-DCS Digital-Coded Squelch	OFF D023N/I-D754N/I (Press # to toggle DCS polarity) Rx (receive) DCS “DPL” decoding for speaker muting.
19	Tx-DCS Digital-Coded Squelch	OFF D023N/I-D754N/I (Press # to toggle DCS polarity) Tx DCS “DPL” encoding during transmit.
20	SC-REV Scan Review	TO CO SE (Timer Carrier Search) Signal detection/monitor behavior while scanning.
21	SP-MUTE Speaker Muting	QT QT*DT QT&DT (Quiet Tone QT or ANI QT & ANI) Require Quiet Tone and/or ANI-ID to unmute speaker.
22	DTMF-ST DTMF & ANI Side-Tones	OFF DT-ST ANI-ST DT+ANI (DTMF ANI-ID Both) Enable hearing DTMF keypad and/or ANI-ID tones during Tx.
23	PTT-ID Transmit Unit ID #	OFF BOT EOT BOTH (B = Beginning, E = End) Send your ANI-ID (Unit #) during Tx with PTT (Push-To-Talk).
24	ID-EDIT Unit Identification	0–9 (ANI-ID up to 6 digits, 3-digit min., use keypad to enter) Automatic Number Identification (Unit #) for Selective Calling.
25	ID-DLY:ms Identification Tx Delay	100MS–3000MS (in milliseconds) Delay before ANI-ID is sent after Tx starts, with PTT-ID.
26	RING:s Incoming Select Call Ringer	OFF 01S–10S (in seconds) Duration of audible ringer before voice, when Rx ANI-ID.
27	ABR-LV Automatic Backlight Level	01–05 (05 is highest brightness) Brightness for automatic LCD backlight.
28	OFFSET (VFO mode only) Tx Offset Frequency	0–999.99750 (in MHz, Only 005.00000 MHz used on GMRS) TX + offset freq. when operating a GMRS repeater.
29	CH-NAME (ch mode only) Channel Alpha-8 Name	! " \$ % & ' () * + , - . / 0-9 : ; < = > ? @ A-Z [\] ^ _ ` a-z { } ~ Enter up to 8 char., #- LOCK =right, EXIT =left, LP EXIT =exit
30	MEM-CH Save Memory Channel	001–999 (3 digits, MENU =write, EXIT =cancel) Write current settings to any used/unused memory channel.
31	DEL-CH Delete Memory Channel	001–999 (3 digits, MENU =erase, EXIT =cancel) Erase any used memory channel.
32	PRI-CH Priority Channel	001–999 (3 digits, MENU =set, EXIT =cancel) Set any used memory channel as the Priority Channel.
33	PRI-SCN Priority Channel Scan	ON OFF Enable Priority Scanning (of the Priority Channel in standby).

Function Menu Options & Descriptions 54–62

54	AM-SW AM Receive Mode Switch	OFF ON (OFF = Normal FM Mode Rx) Disable or enable AM Mode Rx on current memory channel.
55	PF1-DEF SP Prog. Function Key 1 Short	CALLID : TX Group ID Call R-ALARM : TX Remote Siren SOS : Local Emergency Siren SF-TX : Alternate Rec. PTT SCN : Toggle Scan Mode SECOND : Toggle Stopwatch LAMP : Toggle Flashlight K-LAMP : Toggle Backlight
56	PF2-DEF LP Prog. Function Key 2 Long	
57	PF3-DEF LP Prog. Function Key 3 Long	
58	VOLTAGE Battery DC Volts	SHOW HIDE Press MENU to show (for 12 sec.) or hide battery voltage.
59	QT-SW Quiet Tone Scan Switch	OFF ON (ON uses CTC/DCS stored in each channel) Enable CTCSS/DCS speaker muting while scanning.
60	S-MUTE Sub-Receiver Mute Mode	OFF RX-MUTE TX-MUTE R/T-MUTE Mute alternate receiver during Rx, Tx, or both, on MAIN rec.
61	RESET Name	VFO ALL (Menu Functions Menu & Memories – BEWARE!) ALL restores radio to 44-channel Emergency configuration.
62	SCN-MD Color Screen Mode	Classic Covert Day 1 Day 2 Set color Screen Modes. Radio will power-cycle on change.

Visit **BetterSafeRadio.com/UV9GX+** for more information or support, to download a printable PDF version of this manual or the original pre-programmed GMRS SHTF Channel Table, the original KG-UV9P manual (for advanced features), or the free **WOUXUN** Customer Programming Software (CPS) and USB Programming Cable software drivers, to purchase a host of useful accessories such as a high-gain tuned *Smiley Antenna* to extend your operating range, or to post a gear review & provide constructive feedback, which are always appreciated. Thanks & Be Safe!

When the SHTF, BetterSafeRadio than Sorry!™