

The ideal Amateur Mobile/Base Radio

MICOM-H

HF-SSB Digital Signal Processing Radio
125 watt PEP/Average
HF All Band Transceiver



Features

MICOM-H is an advanced Ruggedized Digital Signal Processing transceiver intended for very wide area radio communications. It provides Voice, Data, Fax and E-mail solutions with a high degree of sophistication, signal quality and reliability, while being very simple to operate.

MICOM-H with its compact size provides maximum ease of installation.

Optional:

- ALE Per FED STD 1045 (Where Licensed)
- E-mail over HF with internet gateway

- Enhanced features for better communications
- Ruggedized Mobile / Fixed Transceiver
- Front panel programming
- Advanced digital technology
- Conforms to MIL-STD 810 and EIA Specifications
- High MTBF
- Complies with ISO 9001 Requirements
- Security access code
- Variable Bandwidth for optimal signal processing
- Voice activated digital squelch
- Programmable channel scan
- Digital noise blanking and clarifier
- Guard and Priority Channels
- Continuous duty operation (optional)
- Multi-language Liquid Crystal Display
- BITE (Built-in Test)
- Meets FCC and EMC standards
- Selectable front-end Attenuator
- Enhanced Voice Quality
- Excellent frequency stability
- Selectable Power Output
- Small size, light weight
- Variable notch filter
- Sub-octave pre-selector
- Adaptable internal configuration options
- 200 memory channels
- Variable power output

MICOM-H

HF-SSB Digital Signal Processing radio
125 watt PEP/Average



Power Supply/Charger



Desk Mic



Headset Mic



Speaker

GENERAL																
Model Number:	M82AMN0K0V5-K															
Frequency Range:	Receiver: 100kHz-30.000 MHz Transmit: 1.800-1.999999 MHz, 3.500-3.999999 MHz, 7.000-7.300 MHz, 10.100-10.150 MHz, 14.000-14.350 MHz, 18.068-18.168 MHz, 21.000-21.450 MHz, 24.890-24.990 MHz, 28.000-29.700 MHz															
Number of Channels:	200: User programmable; Simplex or Half Duplex															
Scanning:	5 groups with up to 100 channels per group															
Frequency Stability:	0.6 PPM, (0.1 PPM optional)															
Frequency Drift (Aging):	1 PPM per year															
Synthesizer Lock Time:	10 msec max.															
Frequency Resolution:	10 Hz															
Audio Bandwidths @ -6dB:	Voice: 350 to 2700 Hz CW: 650 to 1150 Hz Low speed data: 1450 to 1950 Hz High speed data*: 350 to 3300 Hz															
Operating Temp. Range:	-30° to +60°C															
Humidity:	95% @ 50°C															
Operating Voltage:	13.8V DC ± 20% Neg. Ground															
Current Drain @ 13.8 VDC	<table border="1"> <thead> <tr> <th colspan="2">Receive</th> <th colspan="3">Transmit</th> </tr> <tr> <th>Squelched</th> <th>Full Audio</th> <th>Voice</th> <th>2 Tone</th> <th>1 Tone</th> </tr> </thead> <tbody> <tr> <td>2.2A</td> <td>3A</td> <td>14A</td> <td>23A</td> <td>28A</td> </tr> </tbody> </table>	Receive		Transmit			Squelched	Full Audio	Voice	2 Tone	1 Tone	2.2A	3A	14A	23A	28A
Receive		Transmit														
Squelched	Full Audio	Voice	2 Tone	1 Tone												
2.2A	3A	14A	23A	28A												
Dimensions and Weights	Height mm/inch	Width mm/inch	Depth mm/inch	Weight Kg Lb												
	92 / 3.7	302 / 11.9	270 / 10.7	5.7	12.5											

RECEIVER	
Sensitivity (SINAD) SSB: (Voice)	0.5 μv for 10 dB SINAD (0.3 μv Typical. Note 1) 0.1-1.6 MHz – reduced performance
1/2 Rated Power Sensitivity:	1 μv for 2.5W audio @ speaker
Selectivity:	-6 dB @ 350 to 2700 Hz -60 dB @ -1 kHz, +4 kHz
Image Rejection:	-80 dB
IF Rejection:	-85 dB
Undesired Sideband Rejection:	-55 dB @ -1 kHz
Spurious Rejection:	-80 dB
Intermodulation Rejection:	-80 dB
Cross Modulation Rejection:	-100 dB @ 100 kHz
Desensitization:	-100 dB @ 100 kHz
Reciprocal Mixing:	-100 dB @ 100 kHz
Audio Power @ Speaker:	5W @ 2.5% distortion
RGC Range:	5μv/1V (2 dB change in output level)
RGC Time Constants Voice:	Attack time 10 msec Release time 1500 msec
Data:	Attack time 10 msec Release time 10 msec
Squelch:	Constant SINAD (digital)
Clarifier Range:	± 200 Hz in 10 Hz steps
Receiver Tuning Adjustments:	None
Preselector Sections:	Sub-octave (1.6 MHz to 30 MHz range)
Antenna Input Protection:	20 kV maximum transient, 100V RMS for 2 minutes

TRANSMITTER	
Output Power:	125W P.E.P. and average
Reduced Power Levels:	25W, 62W, 100W (RSS Programmable)
Audio Bandwidth Ripple:	3 dB
Intermodulation:	-31 dB/P.E.P. (-35 dB/P.E.P. Typical. Note 1)
Harmonic Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical. Note 1)
Spurious Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical. Note 1)
Carrier Suppression:	-50 dB/P.E.P.
Undesired Sideband Suppression:	-55 dB/P.E.P.
Audio Distortion:	2.5%
1/2 Power Mic. Sensitivity:	25 to 125 mV (RMS)/600 ohms
Hum & Ripple:	-50 dB
Inband Noise:	-60 dB (30 Hz BW)
Tx/Rx Switching Time:	10 msec
Tx Tuning Adjustments:	None

Note 1: Values noted as typical are valid over 90% or more of the frequency range.

MILITARY & INDUSTRIAL STANDARDS			
MICOM-H meets the following US military and industrial standard requirements for adverse environmental conditions (without the need of external shock mounts)			
Environmental Condition	US Military STD 810C	US Military STD 810D	US Military STD 810E
Vibration	Method 514.2	Method 514.3	Method 514.4
Shock	516.2	516.3	516.4
Rain	506.1	506.2	506.3
Dust	510.1	510.2	510.3
Salt Fog	509.1	509.2	509.3
The MICOM-H also meets the EIA-RS152B for shock, vibration and applicable test procedures, US FCC for channel occupancy, spurious, interference and frequency tolerance. It is manufactured according to the demanding standards of ISO 9000 and EMC (Electromagnetic Compatibility).			
FCC Information: Emissions:	J3E, R3E, H3E, J2A, J2B, B8C		
FCC Applicable Parts of Rules:	15, 80, 90		
FCC Type Acceptance Number:	ABZ9QCC1635		
With High Stability Option:	ABZ9QCC1634		

- | OPTIONS | |
|----------------------------------|-----------------------|
| ● RS232 Remote Control Interface | ● Interlink Interface |
| ● Linear Amplifier Interface | ● 24 VDC Operation |
| ● Phone Patch Interface | ● RSS for PC |
| ● Data/Fax Modem interface | |
| ● MicomNet-Internet gateway | |
| ● ALE | |

- | MAJOR ACCESSORIES | |
|------------------------------|------------------------------|
| ● Phone Patch | ● Antennas and Grounding kit |
| ● Interlink (FM-HF repeater) | ● Data/Fax Modem |
| ● Automatic Antenna Tuner | ● CW Key & Headphones |
| ● Continuous Duty Kit | ● Mobile Mounting kit |
| ● AC Power Supply | |
| ● Micom Tel | |

Specifications subject to change without notice.

Motorola - U.S.
Federal Government Markets Division
7230 Parkway Drive, Hanover, MD 21076
Tel: 410-712-6211
Fax: 410-712-6208
E-mail: C11506@email.mot.com

USA Sales Office
MOBAT/T.G.Inc. PO.Box 270238
St. Louis, MO 63126
Tel: 636-343-8801, Fax: 636-343-8853
Toll Free: 1-877-343-8801
E-mail: MOBATTG@aol.com

Royal Communications International
12271 Stonemill Drive
Poway, CA 92064
Tel: 858-271-8583
Tel: 858-271-8593
E-mail: RC1888@AOL.com

Motorola - Latin America
Markets Division
8000 West Sunrise Blvd.,
Plantation, FL 33322
Tel: 954-723-8602
Fax: 954-723-8560
E-mail: BUSR56@email.mot.com

Motorola - Asia-Pacific Ltd.
Innovation Centre -level 7
12 Ang Mo Kio St. 64, Ang Mo Kio Ind. Park 3
Singapore 569088
Tel: (65) 481-7200
Fax: (65) 481-9282
E-mail: shlomo.liberman@motorola.com



MOBAT Communication Ltd.
6 Ha'amal St. P.O.B. 1250
Ind.Zone Bat-Yam 59112, Israel.
Tel: 972-3-551-5955
Fax: 972-3-552-0579
E-mail: rfitin@mobat.com
www.mobat.com



www.mot.com/hfssb